

UK



RWS SPECIAL



		n. utili vasca AxBxC mm. t tank sizes AxBxC mm.		Carica di Sfere Kg. Steel balls load Kg.
RWS-1220-G/CF	65	985 x 220 x 330 mm.	4,12	180 - 200 Kg.
RWS-1300-G/CF	100	960 x 285 x 400 mm.	5,5	230 - 260 Kg.
RWS-1450-B-G/CF	225	1000 x 450 x 560 mm.	6,0	650 - 850 Kg.
RWS-80x45-G/CF	155	780 x 455 x 485 mm.	6,0	400 - 500 Kg.
RWS-130x60-B-G/CF	495	1300 x 600 x 700 mm.	11,25	1400 - 1800 Kg.
RWP-S-150-P/CF	150	875 x 355 x 495 mm.	4,0	350 - 400 Kg.

The series Special RWS offers special machines for polishing high-frequency, Rollwasch[®] was the first in the world to produce machines at 3.000 rpm.

The various models of series the Special RWS is characterized by a high power and efficiency of the vibratory motion at high frequency (3,000 rpm), thus resulting in exceptional polishing results in a short time. Particularly powerful are the dual-engine versions, with vibratory-pads able to develop a very high centrifugal force, ensuring leading results.

Special machines are a "classic" line of Rollwasch®.

2

RWS SPECIAL





The series Special RWS offers special machines for polishing high-frequency, Rollwasch[®] was the first in the world to produce machines at 3.000 rpm.

Series Special RWS (like other series of Rollwasch[®] machines with rectangular tank) provides the possibility to adopt optional bulkheads for the subdivision of the tank into sections. Articles processed in between of these bulkheads in the tanks, will remain in place (eg, an aluminum wheel in vertical position). Photo 1: a bowl with 2 bulkheads; Photo 2: with 3 bulkheads; Photo 3: 7 with bulkheads; Photo 4: a detail of the bulkheads in polypropylene;

3



RWS SPECIAL





RWS-130x60-B-G/CF

Example of filter

The Series Special RWS offers machines that can attain, in the case of 130x60, over 2.000 kg. between balls and pieces.

Thousands of machines Special RWS have been sold by the 60s / 70s and today and see this type of machines, the protagonist of several applications of the ball-burnishing process.

Examples include metal items of different kind and nature, from the trays such as "gastronorm" in stainless steel, cast aluminum components for all forms and types, components in copper and bronze. The ballburnishing is a process that, beyond the investment, offers very low cost.

RWP Special









Sound-absorbing lining

Among the various models for ball-burnishing at 3,000 rpm are, as "entry level", the type RWP-S-150-P/CF, competitive and handsome.

RWP-S-150-P/CF born with an antiabrasive polyurethane coating of the tank with suitable hardness for ballburnishing processes. This solution represents the entry-level machine for ball-burnishing at 3000 rpm. and is offered with optional cabin, electric switch type magnetothermic (on/off) or, alternatively, with control panel complete with timer.









All machines series Special RWS can be supplied with magnetothermic switch or, alternatively, with control board with process timer.



RWS Special







SPECIAL RWS-130x60-B-G/CF



All machines series Special RWS can benefit from a program of optional accessories very useful, including the acoustic cabins.

7



VIA SAN CARLO, 21 20847 Albiate (MB) - Italia



TEL. +39 0362 930334 Fax. +39 0362 931440 E-Mail Info@rollwasch.it



WWW.ROLLWASCH.COM PERFECT SURFACES SINCE 195



