

SUPER-VIBROBLAST

S-VBA-DP

VIBROBLAST
TECHNOLOGY - VBT

OUR EXPERIENCE, YOUR RESULTS





 **DELTA**

AUTOMATICO

ALLARMI

Ricetta
in uso

1

VIBROBLAST VBA-DP

VIBRO-BLASTING AUTOMATIC PROCESSES

RESET

RICETTE

IN CORSO

PARAMETRI

Totale tempo
impostato

min
33

sec
15

MANUALE

Totale tempo
rimanente

min
33

sec
15

IT

SUPER VIBROBLAST

S-VBA-DP



VIBROBLAST S-VBA-DP
GREAT EFFICIENCY AND
MAXIMUM RELIABILITY



VIBROBLAST S-VBA-DP HIGH PERFORMANCE

Vibro blast
Air

ROLL
WASCH

SUPER VibroBLAST-AIR - S-VBA-DP3-120-TN-EXS-WS

CE
Made in Italy

SUPER VIBROBLAST

S-VBA-DP




VIBROBLAST S-VBA-DP

VIBRO-BLASTING
PLUG & PLAY SYSTEM





SUPER VIBROBLAST S-VBA-DP



S-VBA-DP3-120-TN-EXS-WS

Vibro blast
Air

ROLL
WASCH

SUPER VibroBLAST-AIR - S-VBA-DP3-120-TN-EXS-WS

The **Super VibroBLAST Air DP** line is designed and manufactured to be supplied on a technological pallet, to make its installation immediate through a simple **plug-&-play** operation. It is enough to connect air (6 Bar) and the Euro socket to the designated line and the machine can start working as it was programmed during the try-out phase before shipment.

We take particular care of manufacturing quality, safety and ergonomics.

SUPER VIBROBLAST


S-VBA-DP



VibroBLAST AIR model	#/Ø mm Port.	Vibr. Machine	Air cons. lt/1' bar	HP cyclone	Cyclone Met. alloy	Nr.Nozzles	Dust collector Filt.surf. cm ²	Filter cleaning	Air Snorkles TOP-Blast	PneuPORT unloading port	Control board
S-VBA-DP3-060-TN-EX	Ø 98	SM3-D3-60	780x2 (6)	0,75	Steel	2	24.000	Manual	3	-	TCS-svba-1
S-VBA-DP3-060-TN-EXS-X	Ø 98	SM3-D3-60	780x2 (6)	0,75	SS	2	24.000	Autom.	3	-	TCS- svba -1
S-VBA-DP3-120-TN-EX	Ø 98	SM3-D3-120	780x2 (6)	0,75	Steel	2	24.000	Manual	3	-	TCS- svba -2
S-VBA-DP3-120-TN-EXS-X	Ø 98	SM3-D3-120	780x2 (6)	0,75	SS	2	24.000	Autom.	3	-	TCS- svba -2
Letters: -DP2	second additional filter in the door										
Letters: -SN	SIDE-NOZZLE nozzle placed sideways										
Letters: -EX	Standard dust collector is replaced by a filter with characteristics comparable to Atex internal zone 22 – 24.000-cm ² filtering surface										
Letters: -EXS	Like -EX with automatic shaking of filtering cartridges in counter-current compressed air – complete with microprocessor for cleaning intervals programming – 90.000-cm ² filtering surface. Industrial vacuum cleaner 0,75KW										
Letters: -EXS2	Like -EX with automatic shaking of filtering cartridges in counter-current compressed air – complete with microprocessor for cleaning intervals programming – 90.000-cm ² filtering surface. Industrial vacuum cleaner 2,2KW										
Letters: -EXS2L	like -EX2; L= low (rotary motor plus motorization placed below for easy maintenance)										
Letter: -X	The standard version includes a carbon steel cyclone; the extension X instead identifies the replacement of the standard cyclone with one in stainless steel and air/sand mixing unit in Polyurethane instead of aluminium;										
Letters: -AS	Antistatic system for polymers										
Letters: -WS	WS (Wear Sensor) – Techno Surface patent – to report, well in advance, that the working tank is worn and needs to be replaced or a new anti-abrasive coating										
Letters: -MS	Addition, on each sand supply line to the nozzle, of a media or sandblasting grit flow rate sensor (Media Flow Rate Sensor) specific for non-metallic media/grits and for vacuum systems										
Letters: -FS	Flow detector sensor complete with cables										
Letters: -SM	SIEMENS main control board instead of standard main control board (Delta)										
Appendix: -7 or -15	The standard touch screen (or HMI) is of 4,3" – on demand a bigger HMI – 7" or 15" - can be supplied. If there is the cabin, the panel is placed on the external operator side										
Letters: -AM	AM Cabin - with 7 doors and relevant RFID sensors – On the operator side of the cabin is foreseen a set-up to combine the same HMI (touch screen) foreseen on the machine										
Letters: -SB	available from October 2024; specific version with safety perimeter and access delimited by perimetral barriers										
Letters: -PL	available only combined with SB version; it allows to raise and lower the sandblasting guns' holder bars through a pneumatic piston										



The STANDARD version of S-VibroBLAST machines will be with vertical nozzles TN (Top Nozzle). Given some qualitative results obtained in specific domain (micromechanics), it is not excluded to apply the solution with lateral nozzle SN (Side Nozzle) to all clients who will demand it or where it is priority to treat pieces with a certain delicacy.



The **VibroBLAST AIR DP** (Vacuum or Depression) **VBA-DP** program is particularly competitive and versatile.

The **VibroBLAST AIR PR** (Pressure) **VBA-PR** program is particularly efficient and effective.

The **VibroBLAST WET - VBW** program is particularly specialized for some types of applications.

VibroBLAST - Air (Patent pending - I) DP (depression)

The **Rollwasch**[®] program for dry sandblasting with vibrofinishing machines offers new horizons to your expectations. The standard **VibroBLAST - Air** (Patent pending - I) program consists of models available both with depression (**DP**) and pressure (**PR**) technology.


This brochure is only about **DP** models. The range of machines starts with nominal capacities of 60 and 120 litres with blasting nozzles involving in 3D the mass-loaded parts in the vibratory finishing unit.

[1] **AS**: Antistatic system for polymers
 [2] With **VibroBLAST** you do not use your hands to sand one piece at a time! Sandblasting takes place in mass and in **3D** inside a vibratory finishing machine (Patent pending I).



S-VBA-DP

S-VBA-DP3-120-TN-EXS-WS




SUPER VIBROBLAST

S-VBA-DP

S-VBA-DP3-120-TN-EXS-WS



CRONOLOGIA REVISIONI			
REV	DESCRIZIONE	DATA	AUTORE
1	Modificato attacco pistole	12/01/2024	Annoni M



**ROLLWASCH®
ITALIANA SPA**

Our experience, your results!

Uffici e stabilimento / Offices and workshop: Via San Carlo 21, 20847 ALBIATE (MB) - Italy
www.rollwasch.it - e-mail: info@rollwasch.it - Tel.: +39 0362 930334 - Fax: +39 0362 931440
 e-mail diretta ufficio tecnico / direct e-mail of technical department: uftec@rollwasch.it

Le tolleranze consequenziali non devono essere cumulative						
Scostamenti per le quote senza indicazione di tolleranza	grado di precisione	da 0 mm			angolari	
		a 6 mm	a 30 mm	a 120 mm	dim lato più corto	0.9 mm ogni 100mm
tolleranza		±0,1	±0,2	±0,3	±0,6	±0,8

Macchina

Descrizione **S-VBA-DP3-120-TN-EXS-WS**

Diritti di autore e di proprietà intellettuale riservati - A termine di legge ci riserviamo la proprietà di questo disegno con divieto di riprodurlo o renderlo noto a terzi senza autorizzazione.
 Copyright and intellectual property rights reserved - By law we reserve the ownership of this design with prohibition to reproduce it or make it known to third parties without authorization.


Materiale	
Trattamento	
Verniciatura	
Saldature	
Note	Dove non indicato saldature continue
Scala:	1 : 10
Disegnatore	Giovanni M.
Visto	GIO
Sostituisce il:	
Sostituito da:	
Disegno N°	VA0040000A1



SUPER VIBROBLAST

S-VBA-DP


S-VBA-DP3-120-TN-EXS-WS




All **Super VibroBLAST Air DP** systems are the result of careful design being characterized by: A) two sandblasting nozzles; S) three air inlet snorkels; B) filtered dust collection container - on the same side as C) cyclone loading door for sandblasting media; D) side for total discharge from the tank door; M) two air-sand mixing groups (see specifications on page 11); R) three connections for filtered sand discharge, in correspondence with the three filters on the tank bottom; L) InterLock - safety lock on shot nozzles support bars; P) protective panel; Hepa) the filter aspirator is equipped with a standard filter M (1 micron) and an outlet silencer.

SUPER VIBROBLAST

S-VBA-DP



S-VBA-DP3-120-TN-EXS-WS



2 «IN»

3 «OUT»

The Super VibroBLAST Air DP system includes two tilting bars to support the two sandblasting nozzles. In this representation the bars are raised, an operation performed manually by the operator only at the end of the work cycle - in this case the safety interlock releases the constraint to be able to tip over the bars upwards. The operator will thus be able to open the access cover to the work tank and start it where required for loading and unloading operations, without the risk to activate the sandblasting nozzles - they are in fact inhibited by the interlock sensor.

Once the cover is closed and the bars are lowered with the interlock active, the sandblasting nozzles can be activated in complete safety - there are two protective bellows around the cover upper holes;



SUPER VIBROBLAST S-VBA-DP





All **Super VibroBLAST Air DP** systems have been designed to ensure excellent aspiration and filtration, with ATEX Zone level 20 or 22 inside the aspiration unit.

To increase its performance, the basic machine is painted with a new type of glossy paint to minimize dust sticking to the internal walls. The air exhaust collector is equipped with a silencer. **Super VibroBLAST** systems can be equipped with the automatic shaking – all three exhaust collectors of relevant filters on the bottom of the tank are equipped with an air inlet in order to facilitate sandblasting powders and grains evacuation. It is always recommended to use dried compressed air (without moisture).

SUPER VIBROBLAST

S-VBA-DP

ROLL
WASCH



All **Super VibroBLAST Air DP** systems have TN (Top Nozzle) sandblasting nozzles placed in the cover upper area, to involve from above the treated components, while they rotate three-dimensionally, clockwise, inside the circular vibro-blasting tank.

At the apex of the cover, we therefore have the nozzle [1] with vertical adjustment [2], placed above the mass being processed [3]. The cover S-VBA includes 3 snorkles [S].

The presence of 3 discharge filters [4], instead of the single filter in the basic version, allows the Super VibroBLAST to carry out treatments with pressures of up to 6 bar with the certainty of a total and effective discharge of the sandblasting media.

At the same time, the components subjected to vibro-sandblasting meet the nozzles every 180°, instead of every 360° as in the basic version.



SUPER VIBROBLAST

S-VBA-DP





All **Super VibroBLAST Air DP** systems have been designed to ensure, where required, a stainless-steel cyclone feeding the sandblasting media, as an alternative to that of painted carbon steel. This happens, for example, in sectors such as medical, food or all contexts in which this solution is necessary.

At the same time, with the standard cyclone in painted carbon steel, the (2) air-sand mixing groups mounted under the lower cone are made of aluminium.

In the version with stainless-steel cyclone, the two mixing groups are made of non-toxic and anti-abrasive polyurethane, with stainless-steel fittings and inserts.

SUPER VIBROBLAST

S-VBA-DP... ...SB





SB Version (Safety Barrier) – available from October 2024; specific version with safety perimeter and access delimited by perimetral barriers.

PL Version (Pneumatic Lift) – available only combined with SB version; it allows to raise and lower the sandblasting guns' holder bars through a pneumatic piston.





SUPER VIBROBLAST

S-VBA-DP





S-VBA-DP3-60-TN-EXS-WS-AM



SUPER VIBROBLAST

S-VBA-DP



S-VBA-DP3-60-TN-EXS-WS-AM

	<h1>ROLLWASCH® ITALIANA SPA</h1>		Materiale Trattamento Verniciatura Saldature	
	Our experience, your results!		Note: Dove non indicato saldature continue	
Uffici e stabilimento / Offices and workshop: Via San Carlo 21, 20847 ALBIATE (MB) - Italy www.rollwasch.com - e-mail: info@rollwasch.it - Tel.: +39 0362 930334 - Fax: +39 0362 931440 e-mail diretta ufficio tecnico / direct e-mail of technical department: uftec@rollwasch.it		Scala: 1 : 25	Data: 09/10/2023	
		Disegnatore Marzagalli G.	Visto GIO	
		Sostituisce il:		
		Sostituito dal:		
		Disegno N° VA0060000A2		
Le tolleranze consequenziali non devono essere cumulative				
Scostamenti per le quote senza indicazione di tolleranza	grado di precisione tolleranza	da 0 mm a 6 mm ±0,1	6.01 mm a 30 mm ±0,2	30.01 mm a 120 mm ±0,3
			120.01 mm a 315 mm ±0,6	oltre 315 mm ±0,8
			angolari dim lato piu corto 0,9 mm ogni 100mm	
Macchina S-VBA-DP3-60-TN-EXS-WS-AM				
Descrizione				
Diritti di autore e di proprietà intellettuale riservati. All rights reserved. We reserve the property of this design with prohibition to reproduce it or make it known to third parties without authorization. Copyright and intellectual property rights reserved. All rights reserved. We reserve the property of this design with prohibition to reproduce it or make it known to third parties without authorization.				



SUPER VIBROBLAST

S-VBA-DP



SUPER VIBROBLAST

S-VBA-DP





VIA SAN CARLO, 21
20847 ALBIATE (MB) - ITALIA



TEL. +39 0362 930334
FAX. +39 0362 931440
E-MAIL INFO@ROLLWASCH.IT



WWW.ROLLWASCH.COM
PERFECT SURFACES SINCE 1950

OUR EXPERIENCE, YOUR RESULTS

